

Clack®

WS1.5CI

**WATER
SPECIALIST
CONTROL
VALVE**



- 1.5" top mount control valve suited for mid-size commercial/industrial applications
- Lead free brass valve body
- Economical stainless steel optional meter assembly
- Service flow rate of 265 lpm (15.9 m3/h) (70 gpm), backwash 197 lpm (11.8 m3/h) (52 gpm)
- Solid state microprocessor with easy access front panel settings
- Front panel display for time of day, days until next regeneration, volume remaining and current flow rate
- Four methods to initiate the downflow regeneration; meter immediate, meter delayed, time clock delayed or pressure differential
- Program in ppm, French degrees, German degrees, or cubic meters
- Fully programmable regeneration cycle sequence (maximum 9)
- Programmable regeneration cycle times
- Days override feature; 1-28 days available
- 12-volt output AC Adapter provides safe and easy installation
- Pre or Post treated water regenerant refill
- Low salt alarm
- 24 hour clock
- Coin Cell Lithium battery back-up with a 24 hour carry over
- Patented one piece expanding seal spacer stack assembly U.S. Patent 6,402,944
- Patented linearly reciprocating piston operation U.S. Patent 6,444,127
- Patented quiet drain line flow control assembly U.S. Patent 6,776,901
- Reliable and proven DC drive



Optional 1.5" Meter

Water Specialist 1.5" CI Control Specifications

Inlet/Outlet (1)	1.5" Female BSPT or NPT
Cycles	up to 9
Valve Material	Lead free brass
Regeneration	Downflow

CONTROL VALVE FLOW RATES

Service @ 1 bar/15 psi drop (includes meter)	265 lpm (15.9 m³/h) (70 gpm)
Backwash @ 1.7 bar/25 psi drop	197 lpm (11.8 m³/h) (52 gpm)

OPERATING PRESSURES

Minimum/Maximum	1.4 - 8.6 bar (20 - 125 psi)
-----------------------	------------------------------

OPERATING TEMPERATURES

Minimum/Maximum	4° - 43° C (40° - 110° F)
-----------------------	---------------------------

METER SPECIFICATIONS

Accuracy	± 5%
Flow Rate Range	2 - 284 lpm (0.5 - 75 gpm)
Volume Range	0.02 - 5,700 m³
Totalizer	1 - 99,999 m³ (264 - 26,417,000 gallons)

DIMENSIONS & WEIGHT

Distributor Pilot	
Valve bodies with 1.5" Female BSPT Inlet & Outlet	50 mm OD
Valve bodies with 1.5" Female NPT Inlet & Outlet	1.90" OD (1.5" NPS)
Drain Line Connection(2)	1.25" Female NPT
Adapter Included	¾" Male NPT Elbow
Brine Line Connection	¾" Female NPT
Adapter Included	½" OD Poly Tube Compression
Mounting Base	4" - 8 UN
Height From Top Of Tank	191 mm (7.5")
Shipping Weight With Meter	9.5 kg (21 lbs.)

ELECTRICAL SPECIFICATIONS

	AC Adapter	
	International	U.S.
Supply Voltage	230V AC	120V AC
Supply Frequency	50 Hz	60 Hz
Output Voltage	12V AC	12V AC
Output Current	500 mA	500 mA

TANK APPLICATIONS

Water Softener	12" - 30" Diameter (4)
Water Filter (3)	12" - 30" Diameter

CYCLES OF OPERATION

Choose up to nine regeneration cycles, in any order, with a wide range of available values:

Cycle	Range of values
Backwash	1 - 120 minutes
Rinse	1 - 120 minutes
Pause (service)	1 - 480 minutes
Brine (co-current)	1 - 180 minutes
Refill (softener)	0.05 - 95.00 Kg
Refill (filter)	0.05 - 95.00 Liters

Options: Backwash Filter, Weather Cover

Compatible with the following typical concentrations of regenerants or chemicals: Sodium chloride, potassium chloride, potassium permanganate, sodium bisulfite, chlorine and chloramines

1. See Distributor Pilot.

2. Casting comes with a 1.25" Female NPT drain connection. An adapter is provided to accept existing WS1 drain line ¾" Male NPT flow controls up to 38 lpm (10 gpm). Other drain line flow controls are available for flow rates above 38 lpm (10 gpm).

3. Filter tank size calculated @ 407 lpm per m² of bed area/10 gpm of backwash per square foot of bed area

4. Requires a V3158-02 installed for a brine elbow on the control valve, use of a 454 controlled flow brine valve assembly H7070-36CF-5 or H7070-54CF-5 (designed with 5gpm BLFC) , 1" air check, or 494 brine valve assembly, and minimum ¾" hard pipe PVC brine line.