

Clack®

WS1EE

WATER SPECIALIST CONTROL VALVE



- Solid state microprocessor with easy access front panel settings
- Service flow rate of 27 gpm, backwash 27 gpm
- Front panel display for time of day, days until next regeneration, volume remaining, current flow rate and total volume used (Totalizer)
- Four methods to initiate regeneration; meter immediate, meter delayed, time clock delayed or pressure differential
- Optional double backwash feature offers optimum regeneration, cleaning ability and efficiency
- Fully adjustable cycle times with 6-cycle control delivers controlled backwash, downflow brining/slow rinse, second backwash, fast rinse, refill and downflow service
- Coin Cell Lithium battery back-up with a 8 hour carry over
- Backwash and brining ability to 21" diameter tanks
- Downflow regeneration
- 12-volt output AC Adapter provides safe and easy installation
- Control valve design provides optimum service and backwash rates
- Post treated water regenerant refill
- Patented one piece expanding seal spacer stack assembly U.S. Patent 6,402,944
- Patented linearly reciprocating piston operation U.S. Patent 6,444,127
- Patented quiet drain line flow control assembly U.S. Patent 6,776,901
- Reliable and proven DC drive

Water Specialist 1" EE Control Specifications

Inlet/Outlet Fittings..... ¾" to 1.5" NPS
Cycles up to 6
Valve Material Noryl (1) or equivalent
Regeneration Downflow

FLOW RATES

Service @15 psi drop (includes bypass and meter) 27 gpm
Backwash @ 25 psi drop (includes bypass) 27 gpm
Cv Service 7.0
Cv Backwash 5.4

OPERATING PRESSURES

Minimum/Maximum 20 psi – 125 psi

OPERATING TEMPERATURES

Minimum/Maximum 40° – 110° F

METER

Accuracy ± 5%
Flow Rate Range..... 0.25 – 27 gpm
Gallon Range..... 20 – 1,500,000 gallons
Totalizer 1000 - 9,999,000 gallons

DIMENSIONS & WEIGHT

Distributor Pilot..... 1.050" OD Pipe (¾" NPS)
Drain Line ¾" or 1" Male NPT
Brine Line ¾" or ½" OD Poly Tube Compression
Mounting Base..... 2 ½" - 8 NPSM
Height From Top Of Tank..... 7 ¾"
Weight 4.5 lbs.

ELECTRICAL SPECIFICATIONS

AC Adapter

	<u>U.S.</u>	<u>International</u>
Supply Voltage	120V AC.....	230V AC
Supply Frequency	60 Hz	50 Hz
Output Voltage	12V AC.....	12V AC
Output Current	500 mA.....	500 mA

TANK APPLICATIONS

Water Softener 6" – 21" diameter
Water Filter (2) 6" – 21" diameter

CYCLES OF OPERATION (Softener Downflow)

	<u>Softener</u>	<u>Filter</u>
Cycle	Range of time in minutes	
1. Backwash 1 st (upflow)	1-95.....	Backwash 1-95
2. Regenerate Draw/Slow Rinse (downflow)	1-180	
3. Backwash 2 nd (upflow).....	1-95	
4. Fast Rinse (downflow)	1-95.....	Rinse 1-95
5. Regenerant Refill (in service with treated water).....	0.1-99.0 or off	
6. Service (downflow)		

Options: Backwash Filter, Bypass, Weather Cover

Compatible with the following typical concentration of regenerants or chemicals: Sodium chloride, potassium chloride, potassium permanganate, sodium bisulfite, chlorine and chloramines

1. Noryl is a trademark of Sabic Innovative Plastics IP B.V. Company
2. Filter tank size calculated @ 10 gpm of backwash per square foot of bed area